



ESD WRIST STRAP SELECTION CHART

				Singl	e-Wire					
Wristband	Jewel Elastic MagSnaps	Jewel Metal Expansion MagSnaps	Jewel Elastic Adjustable Wrist Straps		Premium Metal Expansion Wrist Straps		Elastic Adjustable Wrist Straps		Lightweight Elastic Adjustable Wrist Straps	Disposable Wrist Straps
Band Material	Silver Expandable metal band elastic nylon		Silver impregnated elastic nylon		Expandable metal band		Silver impregnated nylon		Silver impregnated nylon	Dissipative vinyl
Coil Cord	MagSnap	MagSnap MagSnap		Machined stud / socket, 4mm		chined ocket, 4mm	Machined stud / socket, 4mm		Machined stud / socket, 4mm	N/A
Closure Type	Patented cam-lock		Adjustable metal locking clasp		One size fits all		Adjustable, patented cam-lock		Adjustable, patented cam-lock	Slipknot cinch
Other Feature Replaceable band		Superior skin contact		Choice of cap Jewel colors; contact eplaceable grey band			Replaceable blue band		Lightweight band	For one time use
		<u> </u>		Dua	-Wire				<u> </u>	
Wristband		Jewel Adjustable Dual-Wire MagSnaps Wrist Straps	Dual-Wire Met MagSnaps Dual-\		Jewel Premium Metal Dual-Wire Wrist Straps Elastic Wristband		Jewel Dual Wire Wrist Strap with Adjustable		Elastic Adjustable Dual-Wire Wrist Straps	
Band Material		Silver impregnated elastic nylon	Expandable metal I		Expand	able metal	Silver impregnated elastic nylon		Silver impregnated elastic nylon	
Coil Cord		MagSnap	MagSnap		MagSnap		Two machined studs / socket, 4mm		Two machined studs / socket, 4mm	
Closure Type		Cam-lock opposite buckle	N/A		N/A		Adjustable clasp opposite buckle		Adjustable clasp opposite buckle	
Other Feature		Replaceable band	Superior skin contact		Superior skin contact		Onyx black cla	asp	Comfortable elastic band	
				Singl	e-Wire					
Coil Cords			Jewel Single MagSnap		Jewel Rapid Retraction					
Termination			s	MagSnap / traight banana		socket, nt banana				
Flex Test				>1,000,000	>50,	000,000				
Other Feature			Re	elaxed retraction		e of cord				
Length (ft)				6, 12, 20		, 10				
				Dua	l-Wire					
Coil Cords		Jewel Dual-Wire MagSnap		Jewel Dual-Wire Core			Snap-One D Cord		ual-Wire Dual-Snap Coil Cord	
Termination		MagSnap / right angle ba 3.5mm phono plug	nana	Snap-One 4m 3.5mm phono p			ne 4mm Two		4mm or 7mm sockets 3.5mm phono plug	3
Flex Test		>11,000,000		>11,000,000		>20	,000		>20,000,000	
Other Feature		Compatible w/ 3M & oth brand continuous monito		Compatible w/ 3M brand continuous					npatible w/ 3M & other	
Length (ft)		6, 12, 18		6, 12, 18		6, 12, 18		6, 12		

^{*} per ANSI EOS/ESD S11.11-1993

^{**} per FTMS 101C/4046 *** per ESD S11.31-1994

² per ASTM D1922

³ per ASTM F1249-90